

FIG. 1




FIG.2

FIG. 3

PROVIDE AT LEAST ONE INPUT SOURCES FOR STORING A PRINTABLE MEDIUM PRIOR TO PRINTING.


PROVIDE AT LEAST TWO OUTPUT DESTINATIONS FOR HOLDING OR PROCESSING THE PRINTABLE MEDIUM AFTER THE PRINTING.

SELECT ONE OF THE OUTPUT DESTINATIONS FOR ANY PAGE OF A PRINT JOB IN AT LEAST ONE OF THE INPUT SOURCES PRIOR TO THE PRINTING.


DETERMINE A PATTERN OF MEDIA FEEDS FOR THE PAGES OF THE PRINT JOB TO ACHIEVE A DESIRED APPEARANCE CHARACTERISTIC FOR A PRINT JOB ASSOCIATED WITH THE OUTPUT DESTINATIONS.

DETERMINE MEDIA FEED INSTRUCTIONS FOR ROUTING THE PAGES (E.G., INCLUDING THE PRINTED PAGES AFTER THE PRINTING) OF THE PRINT JOB BETWEEN AT LEAST ONE OF THE INPUT SOURCES AND AT LEAST TWO OF THE OUTPUT SOURCES.


FIG. 4



5 part unprinted tabs



3 part colored media



2 part printed tabs

FIG.5 A




FIG.5 B




FIG. 5C




FIG. 5D




FIG. 6A




FIG. 6B




FIG. 6C

Table 1: Example of a MediaExit Pattern

Page Identifier	Printing Indicator	Output Destination
4	True	second output dest.
8	True	second output dest.
12	True	second output dest.
13	True	first output dest.

FIG. 7A




FIG 7B




FIG 7C

Table 2: Example of a Balanced MediaExit Pattern

Page Identifier	Printed On?	Output Destination
4	True	second output destination
8	False	first output destination
8	True	second output destination
12	False	first output destination
12	True	second output destination

FIG. 7D

Table 3: Example of an Unbalanced MediaExit Pattern

Page	Printed On?	Output Destination
4	True	<JobExit>
8	True	<JobExit>
12	True	<JobExit>
last	False	Output Destination1
last	False	Output Destination1

FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 13.




FIG. 14




FIG. 12.

